






FILE NAME: F-093-Rev-R1.DWG
























FILE NAME: F-093-Rev-R1.DWG














MDT/MT 1,290.00 1,290.00 1,280.00 J-7 1,270.00 1,270.00 1,260.00 J-6 1,249.00 Ground Level Profile 1,250.00 1,240.00 J-5 1,226.00 1,230.00 Elevation 1,220.00 J-4 1,208.00 1,210.00 GI Pipe 80 mm Ø 1,200.00 (Rising main) 1,190.00 1,180.00 J-3 1,167.00 1,170.00 1,160.00 J-2 1,148.00 Pump House 1,145.00 1,150.00 Centrifuge Pump 1,144.50 60 80 100 140 200 220 240 260 280 300 320 340 360 380 20 40 120 160 180 400 Distance (m)











GENERAL NOTES:

- 1. THIS SLD SHOWS THE SCHEME FOR DISTRIBUTION OF THE POWER WITHIN THE PROJECT BATTERY LIMIT & SHALL be READ IN CONJUNCTION WITH ALL OTHER RELEVANT DRGS. RATINGS, SIZES & QUANTITIES OF EQUIPMENTS MARKED AS '*' NEED TO BE CALCULATED / PROVIDED BASED ON SYSTEM REQUIREMENT AS TENDER SPECIFICATIONS. CONTRACTOR SHALL SUBMIT THE EQUIPMENT SIZING CALCULATIONS & CORRESPONDING SWITCH GEAR RATING ALONG WITH THE BID.
- 2. THE CONTRACTOR HAS TO DO DETAIL ENGINEERING OF HV & LV SYSTEM AND WORK OUT THE RATING OF EACH COMPONENT AS PER DESIGN CRITERIA GIVEN IN TENDER & EQUIPMENT SIZING CALCULATIONS AS APPROVED BY ENGINEER-IN -CHARGE.
- HV SYSTEM:
- a) INTER TRIPPING & CLOSING INTERLOCK SHALL BE PROVIDED BETWEEN TRANSFORMER FEEDER (11KV) AND LT PANEL INCOMER (0.415KV) SIDE.
- b) CT /PT UNIT FOR HT METERING AND TVM SHALL BE AS PER DISCOM.
- 4. <u>LV SYSTEM:</u>
- a) <u>ACB</u>
- 415V SWITCHBOARD INCOMER/ BUS COUPLER ACB SHALL BE FP, EDO TYPE WITH MICROPROCESSOR-BASED O/C, S/C & INBUILT E/F AND UV RELEASES.
- ALL OUTGOING ACBS SHALL BE TP, EDO TYPE WITH MICROPROCESSOR-BASED O/C, S/C & INBUILT E/F RELEASES EXCEPT FOR APFC WHICH SHALL BE MDO TYPE WITH THERMAL MAGNETIC RELEASES.
- IN ALL LT SWITCHBOARDS, CURRENT RATING ABOVE 630A SHALL HAVE ACBs.
- ALL ACBS SHALL BE WITH ICS=ICU=ICW=100%.
- b) MCCE
- 415V SWITCHBOARD INCOMER/ BUSCOUPLER MCCB (>=250A) SHALL BE FP FIXED TYPE WITH MICROPROCESSOR BASED O/C, S/C & E/F RELEASES AND OUTGOING MCCB (>=250A) SHALL BE TP FIXED TYPE WITH MICROPROCESSOR BASED O/C, S/C & E/F RELEASES EXCEPT FOR APFC AND WHICH SHALL HAVE TM BASED O/C, S/C & E/F RELEASES WITH EXTERNAL E/F MODULE. ALL INCOMER/ OUTGOING MCCB (<250A) SHALL HAVE TM BASED O/C, S/C & E/F RELEASES WITH EXTERNAL E/F MODULE.
- ALL MCCB SHALL BE WITH Ics=Icu=100%.
- 5. ALL INDICATIONS, SHUNT TRIP/CLOSING COILS OF HT/ LT BREAKERS (VCBS/ ACBS) WILL BE ON 30/110V DC CONTROL SUPPLY. SPRING CHARGING MOTORS OF ALL BREAKERS WILL BE ON 230V AC SUPPLY. IF, DC SUPPLY IS NOT AVAILABLE FROM EXTERNAL SOURCE, IT SHALL BE DERIVED FROM INBUILT DC POWER PACK SUITABLE FOR ACCEPTING 230V AC SUPPLY FROM EXTERNAL SOURCE.
- 6. IN MCC, ALL MOTOR STARTER COMPONENTS RATING SHALL BE SELECTED AS PER MANUFACTURER'S TYPE-2 CO-ORDINATION CHART. MOTOR STARTERS SHALL BE COMPLETE WITH SINGLE PHASING PREVENTER. AMMETERS IN MOTOR FEEDERS SHALL BE PROVIDED WITH SUPPRESSED SCALE UP TO 6 TIMES FULL LOAD CURRENT FOR INDICATING STARTING CURRENT. ALL MOTOR FEEDERS UP TO OR EQUAL TO 5.5 KW SHALL HAVE DIRECT CONNECTED AMMETERS IN Y PHASE & MOTORS GREATER THAN 5.5KW WILL BE PROVIDED WITH ONE CT & AMMETER.
- 7. THE ON, OFF AND TRIP POSITION OF MCCB/ MPCB SHALL BE CLEARLY INDICATED. ROTARY OPERATING HANDLE FOR MCCBs/ MPCBs WITH THE DOOR CLOSED INTERLOCK SHALL BE PROVIDED. ALL MCCB/ MPCB FEEDERS ON ALL PANELS SHALL BE PROVIDED WITH ON/OFF/TRIP INDICATING LAMPS THROUGH AUXILIARY CONTACTS. WHEREVER STARTER FEEDER PROVIDED WITH MPCB BUT WITHOUT OVERLOAD RELAY, MPCB SHALL HAVE INBUILT OVERLOAD PROTECTION FEATURE.
- 8. 110 OR 220V AC CONTROL SUPPLY FOR LT PCC/ MCC SHALL BE DERIVED FROM CONTROL TRANSFORMER(S) OF ADEQUATE RATING. INTERLOCKING BETWEEN TWO CONTROL SUPPLIES SHALL BE PROVIDED SUCH THAT ENERGIZED SECTION CATERS FOR THE NEED OF THE PCC/ MCC PANEL.
- 9. MCCB & MPCB TERMINALS SHALL BE SHROUDED AND SHALL BE DESIGNED TO RECEIVE CABLE LUGS FOR RELEVANT CABLE SIZES.
- 10. ALL INDICATING LAMPS SHALL BE MULTICHIP LED TYPE.
- 11. MULTIFUNCTION METER FOR MEASURING ALL POWER & ENERGY PARAMETERS SHALL HAVE AN ACCURACY CLASS OF 1.0 OR BETTER, WITH RS 485 COMM PORT.
- 12. ALL CONTACTORS / TIMERS SHALL BE DIN RAIL MOUNTED.
- 13. UNDER STEADY STATE CONDITIONS, VOLTAGE DROP IN VARIOUS SECTIONS OF ELECTRICAL SYSTEM SHALL BE LIMITED TO A) CABLES BETWEEN TRANSFORMER SECONDARY TO PMCC 2 % AND B) CABLES BETWEEN PMCC TO MOTOR- 3%. UNDER MOTOR STARTING CONDITIONS, THE CORRESPONDING VOLTAGE DROP SHALL NOT AFFECT THE OPERATION OF THE MOTOR CONTROLS OR THE ABILITY OF THE MOTOR TO START AND RUN EFFECTIVELY AND IN ANY EVENT SHALL NOT EXCEED 15%. FAULT CLEARING TIME TO BE CONSIDERED WHILE SIZING OF CABLES SHALL BE AS A) PCC INCOMER 1 SEC AND B) TRANSFORMER PRIMARY: 0.16 SEC.
- 14. UNLESS SPECIFIED, ALL SWITCHBOARDS SHALL BE FREE STANDING, COMPARTMENTALIZED, EXTENSIBLE ON BOTH SIDES WITH HEIGHT NOT EXCEEDING 2300MM. ENCLOSURE PROTECTION OF SWITCHBOARDS SHALL BE AS PER TENDER.
- 15. WHEREVER APPLICABLE, SEPARATE PANEL FOR HVAC, FIRE AND PLUMPING PUMP WILL BE PART OF RESPECTIVE BOQ.
- 16. WHEREVER APPLICABLE, PROVISION OF ONE-WAY NET METERING SHALL BE PROPOSED IN THE SLD FOR INTEGRATION OF THE SOLAR WITH THE DISTRIBUTION SYSTEM.
 THIS METHODOLOGY NEEDS TO BE VERIFIED WITH THE STATE ELECTRICITY BOARD AND THE SOLAR VENDORS. SOLAR POWER SUPPLY WILL NOT BE ON WHEN DG IS
 ON.
- 17. WHEN TWO DG'S ARE OPERATING IN PARALLEL THEN PROVISION OF NEUTRAL CONTRACTOR INTERLOCKING SHOULD BE SUCH THAT ONLY ONE DG WILL BE EARTHED.
- 18. MCB USED FOR STANDARD NETWORK SHALL HAVE 'C' CHARACTERISTIC CURVE.
- 19. EACH TYPE & RATING OF OUTGOING FEEDER SHALL HAVE 10% SPARE OR MINIMUM ONE NUMBER.

														SIGN. OF CLIENT:-					
														JE	AE	EE	SE		
													'P' (PRELIMINARY) ISSUES ARE NOT TO BE USED FOR CONSTRUCTION / FABRICATION BUT ARE ISSUED FOR LIMITED PURPOSES ONLY AS INDICATED IN THE SMALL	PURPOSE : FOR TENDER ONLY					
;												<u> </u>		DO NOT SCALE					
NS													BLOCK ABOVE THIS BLOCK.				nly by the "Clant": for the		
												18-04-2022	CONSTRUCTION / FABRICATION WORK IS PERMITTED ON 'R' (RELEASED) ISSUES ONLY.	Project under consideration, a submitted herewith. In consider	Control This document contains which is provided for the sole purp protion of receipt of this documen mation in confidence and to not	pose of permitting the recipient to it; unless agreed to in contrary in	evaluate the information the Contract; the recipient		
	KKS	ASB	ASB	·					·	MK	DK		INFORMATION CONTAINED WITHIN 'HOLD' IS NOT	ration; except that there is no obj	there is no obligation to maintain the confidentiality of any information which web information from Tata Consulting Formers Limited, or becomes publicly				
NS													RELEASED FOR CONSTUCTION / FABRICATION. Insure through no fault of recipient, or Tota Consulting Engineers Limited, or in received willbust obligation from a third party uning no abliquion of confidentiality to Tota Consulting Engineers Limited. All Informations are the consulting Engineers Limited.						
DRN	חםאו	DSN	CHD	CV	EL	IC	ME			DE /DM	YDDD	1	IN TIME BEFORE PROCEEDING WITH ANY CONSTRUCTION/	version over rides all and any blad of offers, assumptions, deliverables and contracts submitted verbally (and subsequently communicated in writing) or in writing or otherwise given under any and all previous version/s.					
	DIXIN	DOM			CLEARED			PE/PM A	AFFD	(dd=mm-yyyy)	1	FILE NAME	: 12503A-	-EL-40004	-Rev-P0				

LEGEND					
	LIGHTNING ARRESTER	R	RELAYING		
/ +	ISOLATER WITH EARTH SWITCH	l	INSTRUMENTATION		
≯ ⊦-	ISOLATER WITH D.O.	25	SYNCHRONIZING RELAY		
⊃, ⊢-	FUSE	27/59	UNDER/OVER VOLTAGE RELAY		
Â	CIDCUIT DDEAKED(ACD (ACD)	81	UNDERFREQUENCY RELAY		
\Rightarrow	CIRCUIT BREAKER(ACB/VCB) DRAW-OUT TYPE	(50)	INST. O/C PROTECTION		
	CIRCUIT BREAKER(ACB/VCB)	(50N)	INST. E/F PROTECTION		
Y	NON DRAW-OUT TYPE	(51)	IDMT. O/C PROTECTION		
\frac{1}{2}	мссв	95	TRIP SUPERVISION RELAY		
þ ጉ	мрсв	49W	WINDING TEMP. HIGH INDICATOR WITH ALARM & TRIP CONTACTS		
£	мсв	490	OIL TEMP. HIGH INDICATOR WITH ALARM & TRIP CONTACTS		
‡	CABLE GLAND	63 X	PRESSURE RELIEF DEVICE		
\otimes	INDICATING LAMP	63 T	BUCHHOLZ RELAY		
•	PUSH BUTTON	OSR	OIL SURGE RELAY		
	CURRENT TRANSFORMER (CT)	MOG	MAGNETIC OIL GAUGE		
\bigoplus_{3}	(FIGURE INDICATES NO. OF CT's)	86	LOCK OUT RELAY		
ЛК		SC	SPRING CHARGED		
	POTENTIAL TRANSFORMER	TCH	TRIP CIRCUIT HEALTHY		
(<u>A</u>)	TRANSFARIUER	SP	SERVICE POSITION		
Æ	TRANSFORMER	TP	TEST POSITION		
TVM	TRI VECTOR METER		ELECTRICAL CABINET		
ത്ത	CHOKE	(NEW)	MULTIFUNCTION METER		
AS	AMMETER SELECTOR SWITCH	(MFM)			
A	ANALOG AMMETER	NET	NET ENERGY METER		
<u> </u>	VOLTMETER SELECTOR SWITCH	METER			
\bigcirc	ANALOG VOLTMETER				
ø-0	PUSH BUTTON STATION	TNC	TRIP-NEUTRAL-CLOSE SWITCH (KEY OPERATED)		
E.M.I.	ELECTRICAL — MECHANICAL INTERLOCK	ETPB	EMERGENCY TRIP PUSH BUTTO		
P G A	TWO MOMENTARY CONTACT PB WITH THREE INDICATING LAMPS	‡	CONTACTOR		
	(R = RED, G = GREEN, A = AMBER)	NC	NORMALLY CLOSED		
L−R □	LOCAL REMOTE SELECTOR SWITCH	NO	NORMALLY OPEN		

DETAILED DESIGN CONSULTANCY, HP-SHIVA (PACKAGE CS09)
IRRIGATION, HORTICULTURE, ORCHARDS AND VALUE CHAIN DEVELOPMENT

TYPICAL SLD FOR LIS PUMPING STATION WITH LT/HT METERING GENERAL NOTES & LEGENDS



TATA CONSULTING ENGINEERS LIMITED

MUMBAI

white our rises at end only laid at other, assumptions, delinerates and contracts sateritistal winday (and subsequently communicated in writing or otherwise discussed in writin

TCE FORM NO. 093 R1

P0

ISSUE

SIGN. INITIALS REVISION

SIGN.

INITIALS

REVISION

P0